

Boom Barrier



Features

- Inbuilt micro processor based intelligent controller
- Electromechanical gear motor with integrated
- Electronic limit switches, springs for boom counter weight with adjuster,
- Heavy duty steel body with powder coating,
- Colour-golden yellow,
- Rectangular shaped boom with caps and coverings
- Manual operation by hand in case of power failure

Specification

BRAND	HULK	HULK	HULK	HULK	HULK
MODEL NO	HD-F-D3	HD-F-D4	HD-F-D5	HD-F-D6	HD-F-D (Fast)
OPENING TIME(Sec)	3-6 Sec	3-6 Sec	3-6 Sec	3-6 Sec	1.5 Sec
BOOMLENGTH(MM)	3000 MM	4000 MM	5000 MM	6000 MM	3000 MM
HEIGHT OF BOOM FORM GROUND	800(MM)	800(MM)	800(MM)	800(MM)	800(MM)
CONTROLLER PROTECTING RATING	IP55	IP55	IP55	IP55	IP55
MOTOR POWER SUPPLY	230VAC 50HZ	230VAC 50HZ	230VAC 50HZ	230VAC 50HZ	230VAC 50HZ
POWER	100W	100W	100W	100W	100W
STATING CURRENT	2.6A	2.6A	2.6A	2.6A	2.6A
TORQUE(Nm)	400	400	400	400	400
DUTYUSE	INTENSIVE USE	INTENSIVE USE	INTENSIVE USE	INTENSIVE USE	INTENSIVE USE
OPERATING TEMP	-30 ^o C TO + 60 ^o C	-30 ^o C TO + 60 ^o C	-30 ^o C TO + 60 ^o C	-30 ^o C TO + 60 ^o C	-30 ^o C TO + 60 ^o C
DAILY OPERATING CYCLES (RECOMMENDED)	600	600	600	600	600
Packing size WXLXH (cm) Barrier, Boom	35X106X27, 12x300x12	35X106X27, 12x400x12	35X106X27, 12x500x12	35X106X27, 12x600x12	35X106X27, 12x300x12
Gross weight Barrier, Boom	60Kg, 12Kg	60Kg, 15Kg	60Kg, 15.250Kg	60Kg, 15.500Kg	60Kg, 12.500Kg

LOKPAL INDUSTRIES